



Authorised Sales & Service Distributer-
Supertech industrial Solutions
 Regd Off-D-180 Sec 10,Noida (UP) 201301
 Branch Off-Plot No.517,Sec-12,Vashundra Ghaziabad UP 201012
 Mobile-+91-9718489991 Landline-0120-4996211
 Web-www.sisbharat.com
 Email-Info@supertechindustrialsolutions.com

KÄRCHER



HD 6/15-4 Classic

Single-phase, compact, strong: the service-friendly HD 6/15-4 Classic high-pressure cleaner with a 600 l/h water flow, powerful crankshaft pump, ceramic piston and the latest sealing technology.



1 Durable and robust

- Extra large crankshafts and connecting rods with robust ball bearings.
- Ceramic pistons for reduced wear and tear.

2 Especially easy to maintain

- Wide-opening machine cover for easy access to all service and maintenance-relevant components.
- Large water fine filter for protecting the pump.

3 Improved cleaning performance

- Patented Kärcher power flat jet nozzles: up to 40 percent more impact force than conventional nozzles.
- High area coverage and thorough dirt removal.

4 Excellent mobility

- Large wheels and ergonomic push handle ensure optimal turning manoeuvrability and easy handling.
- The foldable push handle enables space-saving storage.



HD 6/15-4 Classic

- Durable crankshaft pump with ceramic-coated pistons
- Large, transparent water filter
- Infinitely variable pressure regulation

Technical data

| | | |
|-------------------------------|--------------------|------------------|
| Order no. | 1.367-306.0 | |
| EAN code | 4039784858756 | |
| Current type | Ph / V / Hz | 1 / 220-240 / 50 |
| Flow rate | l/h | 450-600 |
| Working pressure | bar / MPa | 70-150 / 7-15 |
| Max. pressure | bar | 190 |
| Max. inlet temperature | °C | 60 |
| Connection load | kW | 3.4 |
| Weight | kg | 52 |
| Dimensions (L × W × H) | mm | 709 × 469 × 1000 |

Equipment

| | | |
|---|-----------|--------------------|
| Spray gun | standard | |
| High-pressure hose | m | 10 / DN 6, 250 bar |
| Spray lance | mm | 850 |
| Power nozzle | ■ | |
| ANTI!Twist | - | |
| Pressure cut-off | ■ | |
| Servo Control | - | |
| Crankshaft pump with ceramic pistons | ■ | |

■ Included in the scope of supply.

Authorised Sales & Service Distributer-
Supertech industrial Solutions
 Regd Off-D-180 Sec 10,Noida (UP) 201301
 Branch Off-Plot No.517,Sec-12,Vashundra Ghaziabad UP 201012
 Mobile-+91-9718489991 Landline-0120-4996211
 Web-www.sisbharat.com
 Email-Info@supertechindutrialsolutions.com

HD 6/15-4 CLASSIC

1.367-306.0

KÄRCHER



| | | Order no. | ID | Max. working pressure | Length | Price | Description | |
|--|----|-------------|------|-----------------------|--------|-------|---|---|
| Standard with unions on both sides | | | | | | | | |
| High-pressure hose, 30 m, ID 8, incl. rotary coupling | 1 | 6.390-293.0 | ID 8 | 315 bar | 30 m | | To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5. | ▲ |
| High-pressure hose, 15 m, ID 8, 315 bar, including rotary coupling | 2 | 6.390-010.0 | ID 8 | 315 bar | 15 m | | With screw connections on both sides, M 22 x 1.5 with bend protection. | ▲ |
| High-pressure hose, 20 m, ID 8, 315 bar, extension piece | 3 | 6.390-031.0 | ID 8 | 315 bar | 20 m | | Screw connections at both ends, M 22 x 1.5, with kink protection. | ▲ |
| High-pressure hose, 10 m, ID 8, 315 bar, extension | 4 | 6.391-342.0 | ID 8 | 315 bar | 10 m | | To extend the operating radius with the high-pressure cleaner. Connection on both sides M22 x 1.5. | □ |
| Longlife 400 with unions on both sides | | | | | | | | |
| High-pressure hose Longlife 400, 15 m, ID 8, including rotary coupling | 5 | 6.389-709.0 | ID 8 | 400 bar | 15 m | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose Longlife 400, 20 m, ID 8, extension | 6 | 6.390-027.0 | ID 8 | 400 bar | 20 m | | with rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose Longlife 400, 30 m, ID 8, including rotary coupling | 7 | 6.390-294.0 | ID 8 | 400 bar | 30 m | | With rotary coupling, 2 x M 22 x 1.5 | ▲ |
| High-pressure hose Longlife 400, ID 8, 400 bar, 1.5 m | 8 | 6.392-282.0 | ID 8 | 400 bar | 1.5 m | | Screw connections at both ends, M 22 x 1.5, with kink protection. Dual layer steel wire reinforced. | □ |
| High-pressure hose 1.5 m, ID 8, including connectors | 9 | 6.390-178.0 | ID 8 | 400 bar | 1.5 m | | 1.5 m high-pressure hose (DN 8, M 22 x 1.5) with kink protection and connectors at both ends. For connecting to hose reels with appropriate connector (M 22 x 1.5). | □ |
| High-pressure hose Longlife 400, 10 m, ID 8, including rotary coupling | 10 | 6.388-083.0 | ID 8 | 400 bar | 10 m | | 10 m high-pressure hose Longlife 400 (DN 8) with rotary coupling, two layer high-strength steel wire reinforced. Connectors at both ends. M 22 x 1.5, with kink protection. | □ |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

Authorised Sales & Service Distributer-
Supertech industrial Solutions
Regd Off-D-180 Sec 10,Noida (UP) 201301
Branch Off-Plot No.517,Sec-12,Vashundra Ghaziabad UP 201012
Mobile-+91-9718489991 Landline-0120-4996211
Web-www.sisbharat.com
Email-Info@supertechindutrialsolutions.com

HD 6/15-4 CLASSIC 1.367-306.0



| | | Order no. | Flow rate | | | | Price | Description | |
|--|---|-------------|-----------|--|--|--|-------|---|---|
| Trigger guns | | | | | | | | | |
| Standard trigger gun | 1 | 9.751-139.0 | | | | | | High-pressure gun for machines of the HD Classic range. With adapter for high-pressure hoses M 22 x 1.5. | ■ |
| EASY!Force Advanced | 2 | 4.118-005.0 | | | | | | Effortless, not energy-sapping: the EASY!Force high-pressure gun uses the recoil force of the high-pressure jet to reduce the holding force for the operator to zero. | □ |
| EASY!Force conversion kit 2 - from machine | 3 | 4.111-051.0 | | | | | | Developed for retrofitting existing high-pressure cleaners from Kärcher: EASY!Force conversion kit 2 with EASY!Force high-pressure gun, spray lance, high-pressure hose and necessary adapters. | □ |
| Quick connect | | | | | | | | | |
| Quick coupling | 4 | 6.401-458.0 | | | | | | For fast changes between different spray lances/accessories. Perfect for Kärcher spray unit, suitable for trigger gun/spray lance interface. With M 22 x 1.5 internal thread. | □ |
| Male coupling | 5 | 6.401-459.0 | | | | | | Hardened stainless steel male coupling for quick coupling 6.401-458. With M 22 x 1.5 external thread. | □ |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

Authorised Sales & Service Distributer-
Supertech industrial Solutions
 Regd Off-D-180 Sec 10,Noida (UP) 201301
 Branch Off-Plot No.517,Sec-12,Vashundra Ghaziabad UP 201012
 Mobile-+91-9718489991 Landline-0120-4996211
 Web-www.sisbharat.com
 Email-Info@supertechindutrialsolutions.com

HD 6/15-4 CLASSIC 1.367-306.0

Authorised Sales & Service Distributer-
Supertech industrial Solutions
Regd Off-D-180 Sec 10,Noida (UP) 201301
Branch Off-Plot No.517,Sec-12,Vashundra Ghaziabad UP 201012
Mobile-+91-9718489991 Landline-0120-4996211
Web-www.sisbharat.com
Email-Info@supertechindutrialsolutions.com

KÄRCHER



| | | Order no. | Max. working pressure | Length | | Price | Description | |
|--|----|-------------|-----------------------|---------|--|-------|---|---|
| Spray lance | | | | | | | | |
| Spray lance 850mm | 1 | 9.751-044.0 | | | | | 600mm zinc-coated spray lance with hand screw connection is suitable for machines of the HD Classic range. Spray lance is non-rotatable. | ■ |
| 250 mm lance, non-rotatable | 2 | 4.760-667.0 | | 250 mm | | | 250 mm stainless steel lance. With manual coupling. Non-rotatable. | □ |
| 550 mm lance, non-rotatable | 3 | 4.760-665.0 | | 550 mm | | | 550 mm stainless steel lance. With manual coupling. Non-rotatable. | □ |
| 600 mm spray lance | 4 | 9.751-140.0 | | | | | 600 mm long, zinc coated spray lance with hand screw connection. Not rotatable. | □ |
| Rotating spray lances | | | | | | | | |
| 600 mm spray pipe, rotatable | 5 | 4.760-664.0 | 300 bar | 600 mm | | | 600 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Spray lance, 840 mm, rotatable | 6 | 4.760-663.0 | 300 bar | 840 mm | | | 850 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| 1050 mm spray pipe, rotatable | 7 | 4.760-660.0 | 300 bar | 1050 mm | | | 1050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| 1550 mm spray pipe, rotatable | 8 | 4.760-661.0 | 300 bar | 1550 mm | | | 1550 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| 2050 mm spray pipe, rotatable | 9 | 4.760-662.0 | 300 bar | 2050 mm | | | 2050 mm stainless steel lance (manual coupling) with ergonomic handle for ease of use and protection. Rotatable 360° under pressure. | □ |
| Angular spray lance | | | | | | | | |
| Spray lance for toilets and rain gutters | 10 | 4.760-073.0 | | | | | Stainless steel lance WC and gutter with nozzle insert. Specially shaped for effective and hygienic cleaning of gutters and toilets. | □ |
| Flexible spray lance | | | | | | | | |
| Flexible lance 1050 mm | 11 | 6.394-654.0 | 210 bar | 1050 mm | | | 1050 mm flexible lance with variable bend from 20° to 140°, ideal for cleaning difficult to reach areas, e.g. gutters. | □ |
| High-pressure M18x1.5 articulated joint | 12 | 4.481-039.0 | 300 bar | | | | High-pressure articulated joint: Thanks to infinite angle adjustment up to 120°, this tool is ideal to effortlessly clean hard-to-reach areas. Simply attach to the spray lance of the pressure washer. | □ |
| Telescopic spray lance | | | | | | | | |
| Telescopic spray lance | 13 | 6.394-690.0 | 225 bar | 5400 mm | | | Can be continuously extended from 1.8 to 5.4 m. For cleaning areas that are difficult to reach, such as ceilings or facades. With integrated HD trigger gun, M 22 x 1.5 connection with rotary coupling. Connection for M 18 x 1.5 nozzles. | □ |
| Strap for telescopic spray pipe | 14 | 6.373-987.0 | | | | | Convenient strap for relief when working with the telescopic spray lance (6.394-690). The burden is optimally distributed on the body and longer periods of use are possible. | □ |
| Gutter cleaner | | | | | | | | |
| Gutter cleaning lance | 15 | 2.642-305.0 | | | | | The lance is suited for cleaning of gutter systems. Because of the shape of the lance and the special nozzle the gutter can be cleaned without removing the cover plates. | □ |
| Undercarriage spray lance | | | | | | | | |
| Underbody lance | 16 | 4.760-245.0 | | 700 mm | | | Stainless steel lance for effective and easy underbody and wheel arch cleaning. Without high-pressure nozzle. | □ |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

HD 6/15-4 CLASSIC

1.367-306.0

KÄRCHER



1, 3-4



2

| | | Order no. | Nozzle size | | | | | Price | Description | |
|-------------------------------------|---|-------------|-------------|--|--|--|--|-------|--|---|
| Power nozzle spray angle 25° | | | | | | | | | | |
| Power nozzle 25° - 036 | 1 | 2.883-821.0 | 36 | | | | | | Fan jet nozzle with 25° spray angle, suitable for large areas and removing stubborn dirt and stains. | ■ |
| HP nozzle spray angle 0° | | | | | | | | | | |
| High-pressure nozzle 0° - 040 | 2 | 2.884-533.0 | 40 | | | | | | High-pressure nozzle with powerful jet for extremely stubborn dirt. | □ |
| Power nozzle spray angle 15° | | | | | | | | | | |
| Power nozzle 15° - 036 | 3 | 2.885-225.0 | 36 | | | | | | Flat stream for stubborn contaminations. | □ |
| Power nozzle spray angle 40° | | | | | | | | | | |
| Power nozzle 40° - 040 | 4 | 2.884-522.0 | 40 | | | | | | Power nozzle with a 40° spray angle and fan jet, suitable for large areas and sensitive surfaces. | □ |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

Authorised Sales & Service Distributer-
Supertech industrial Solutions
 Regd Off-D-180 Sec 10,Noida (UP) 201301
 Branch Off-Plot No.517,Sec-12,Vashundra Ghaziabad UP 201012
 Mobile-+91-9718489991 Landline-0120-4996211
 Web-www.sisbharat.com
 Email-Info@supertechindutrialsolutions.com

HD 6/15-4 CLASSIC

1.367-306.0

KÄRCHER



| | | Order no. | Max. working pressure | Nozzle size | | Price | Description | |
|---------------------------------|---|-------------|-----------------------|-------------|--|-------|--|--------------------------|
| Dirt Blaster, small | | | | | | | | |
| Dirt blaster - more Performance | 1 | 4.767-231.0 | 180 bar | 40 | | | With rotating point jet for more efficient removal: the new performance dirt blaster with nozzle size 040 achieves up to 50% higher cleaning and area performance than its predecessor. | <input type="checkbox"/> |
| Dirt blaster, large | | | | | | | | |
| Dirt blaster | 2 | 4.763-252.0 | 300 bar | 40 | | | The dirt blaster with rotating pencil jet offers 10 times better cleaning performance. Ceramic nozzle and bearing ring for a long service life. Further data: Max. 300 bar, 30 MPa, 85°C. | <input type="checkbox"/> |
| Triple nozzles | | | | | | | | |
| Triple nozzle 036 | 3 | 4.767-148.0 | 300 bar | 36 | | | Triple nozzle with manual nozzle changeover. Convenient spray adjustment. For machines with an injector, the low-pressure flat stream is useful for cleaning agent suction and application. Connection M 18 x 1.5. | <input type="checkbox"/> |

■ Included in the scope of supply. □ Available accessories. ▲ Extension hose.

Authorised Sales & Service Distributer-
Supertech industrial Solutions
 Regd Off-D-180 Sec 10,Noida (UP) 201301
 Branch Off-Plot No.517,Sec-12,Vashundra Ghaziabad UP 201012
 Mobile-+91-9718489991 Landline-0120-4996211
 Web-www.sisbharat.com
 Email-Info@supertechindutrialsolutions.com